

Eaton 276271

Catalog Number: 276271

Main load disconnect Switch with isolation function, highly wear resistant contacts and classified for the use in rail rolling stock, 415 V 40 A, 2P



General specifications

Product Name	Catalog Number
Eaton Moeller series IS Disconnecter	276271
EAN	Product Length/Depth
4015082762711	60 mm
Product Height	Product Width
80 mm	35.4 mm
Product Weight	Compliances
0.201 kg	RoHS conform
Certifications	
EN45545-2	
IEC 61373	

Product specifications

Type

IS. Main load disconnect switch

Application

Switchgear for industrial and advanced commercial applications

Degree of protection

IP40

IP10

Terminals

Lift terminal

Equipment heat dissipation, current-dependent

1.5 W

Imprint/indication

Symbol "arrows"

Lamp socket

Other

Ambient operating temperature - max

40 °C

Ambient operating temperature - min

-5 °C

Built-in depth

69.5 mm

Heat dissipation capacity

0 W

Heat dissipation per pole, current-dependent

1.9 W

Lamp power

0 W

Number of contacts (change-over contacts)

0

Number of contacts (normally closed contacts)

2

Amperage rating

40 A

Color calotte

Other

Resources

Declarations of conformity

[DA-DC-03_IS](#)

Drawings

[eaton-dimensions-mas-is.jpg](#)

[122I171](#)

eCAD model

[ETN.IS-40_2.edz](#)

mCAD model

[DA-CS-is_2p](#)

[DA-CD-is_2p](#)

Wiring diagrams

[IS_2P](#)

Switch type

Other

Rated short-time withstand current (Icw)

1 kA

Voltage type

AC

Lamp type

Other

Number of contacts (normally open contacts)

2

Rated operational current for specified heat dissipation (In)

40 A

Rated operational voltage (Ue) - max

415 V

Rated switching capacity

12.5 kA

Static heat dissipation, non-current-dependent

0 W

Voltage rating - min

240 V

Width in number of modular spacings

2

Number of poles

Two-pole



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia